

Lift:EAX5-8/6 1200x800 RAL5019

Drawing: 104939					
Table Type EAX10	**Number of Cylinders** 1 *psc*	**No. Scissor Height** 1 *psc*	**No. Scissor Length** 1 *psc*	**No. Scissor Width** 1 *psc*	**Labelled Capacity** 500 *kg*
Capacity 500 *kg*	**Installed Stroke** 800 *mm*	**Designed Stroke** 800 *mm*	**Closed height** 200 *mm*	**Length** 1200 *mm*	**Width** 800 *mm*
Lifting Speed 40 *mm/s*	**Max Lowering Speed** |Not Defined| *mm/s*	**Lifting Time** 20 *sec*	**Output** 0.72 *kW*	**Power Supply** 400 AC 3~/N/PE	**Frequency** 50 *Hz*
Rated current 1.7 *A*	**Control voltage** 24 DC *V*	**Power pack location** INT	**Protection class** 55	**Hydraulic oil** ISO 32	**Surface treatment** K2_02
Colour RAL5019	**Category** 3	**Product Standard** |Not Used|	**Platform Shape** Rectangle	**Declaration** IIA	**Cylinder** 65/40-195
Operating Pressure 100 *Bar*	**Idle Pressure** |Not Defined| *bar*	**Oil flow** 2,1 *litre/min*	**Power Pack** F6239-400-50	**Allowed Persons** 0	**Frame Length** 1160 *mm*
Frame Width 600 *mm*	**Operating Temp** -20 - +50 *°C*	**Hydraulic Drawing** 407401	**Electric Drawing** 1108415	**Power Pack Drawing** 0	**Label Compilation** 1105598
Model EAX5-8	**Marco Designation** M0 005080-D1	**Hymo Designation** EAX5-8/6	**Price List Item** Yes	**Price List Ref** EAXC5-8	

Mechanics	Hydraulics	Electrics

Safety	Finish	Usage

PRO-LIFT SOLUTIONS