

Lift:UXC15-10/10 1640x1870 RAL5019

Drawing: 1224200					
Table Type UXC	**Number of Cylinders** 2 *psc*	**No. Scissor Height** 1 *psc*	**No. Scissor Length** 1 *psc*	**No. Scissor Width** 1 *psc*	**Labelled Capacity** 1500 *kg*
Capacity 1500 *kg*	**Installed Stroke** 1000 *mm*	**Designed Stroke** 1000 *mm*	**Closed height** 80 *mm*	**Length** 1640 *mm*	**Width** 1870 *mm*
Load Width 1000 *mm*	**Pallet Size** 1200x1000 *mm*	**Lifting Speed** 71 *mm/s*	**Max Lowering Speed** |Not Defined| *mm/s*	**Lifting Time** 15 *sec*	**Output** 3 *kW*
Power Supply 400 AC 3~/PE	**Frequency** 50 *Hz*	**Rated current** 6.6 *A*	**Control voltage** 24 DC *V*	**Power pack location** EXT, 3M	**Protection class** IP55
Hydraulic oil ISO 32	**Surface treatment** K2_02	**Colour** RAL5019	**Category** 5	**Product Standard** |Not Defined|	**Platform Shape** Special
Declaration IIB	**Cylinder** 65/40-320-465_45GX	**Operating Pressure** 166 *Bar*	**Idle Pressure** 45 *bar*	**Oil flow** 8,4 *litre/min*	**Power Pack** K 3kW 100 S6,0cc 13L 4P
Allowed Persons 0	**Frame Length** 1635 *mm*	**Frame Width** 242 *mm*	**Operating Temp** -20 - +50 *°C*	**Hydraulic Drawing** 1222774	**Electric Drawing** 1220985
Power Pack Drawing 0	**Label Compilation** 1224336	**Model** UXC15-10	**Marco Designation** UXC15-10/10	**Hymo Designation** UXC15-10/10	**Price List Item** Yes
Price List Ref 1189119					

Mechanics	Hydraulics	Electrics
- Upper part of even sheet steel with reinforcement profiles. - Scissors made in solid flat steel for maximum stability and minimum deflection - Bottom frame with mounting holes for bolting - Lifting eye bolts included	- Compact hydraulic unit with working pressure up to 210 bar - Hydraulic unit with oil according to ISO L-HV 32 - Cylinders with hard chrome plated pistons and piston rod greaseable - All couplings in class S	- All electric to terminal box - Standard motor in IP55 - Protection class IP65 for E-parts - Adjustable upper limit switch
Safety	**Finish**	**Usage**
- Pipe burst safety valve in the cylinder - Safety support legs for maintenance - Signs with pictograms Security Notice - Operating and maintenance instructions included	-Lifting tables are powder coated	- Duty cycles: the scissor lift is based on 25 cycles/hour on 3 shift(s) and 5 days per week - Working Temperature: -20°C to +50°C

PRO-LIFT SOLUTIONS