


F	DIM M4, MAX HOL COLUMN ADDED. TROLLEY MOTOR POWER AMENDED. REF ECO-00562 WHEREVER DIM H = 20 WAS 15. AMENDED AS PER MODEL.	PAK	26/02/2014	Street Crane Co. Ltd				TITLE LX032 CHAIN HOIST CE DATA SHEET ELECTRIC TRAVEL (TYPE 'CE')		CONTRACT No.					
E	MODEL CODE UPDATED TO MATCH NEW PRICE LIST. REF ECO-00552	MAP	10/12/2013							PART No.		DLX-1016			
D	SHT 1 REMOVED. 2000Kg MODEL MOVED TO DLX 1015. REF ECO-00515	GDM	16/07/2013							DRAWING No.		3	DLX-1016	F	SHT 1 OF 3
C	VERSION 'A' & 'B' SWAPPED. REF ECO-00445	SW	16/05/2011							DATE		23/09/2010	DRAWN		SW
B	DIMENSION LAYOUT CHANGED. REF ECO-00429	ANIL	07/02/2011							CHECKED		CR	SCALE		NTS
REV	DESCRIPTION	BY	DATE	DATE		23/09/2010	DRAWN		SW	CHECKED	CR	SCALE		NTS	

INFRINGEMENT OF COPYRIGHT. THIS DRAWING IS THE PROPERTY OF STREET CRANE COMPANY LTD AND MUST NOT BE COPIED OR SHOWN TO THIRD PARTIES WITHOUT THE WRITTEN PERMISSION OF STREET CRANE CO LTD, CHAPEL-EN-LE-FRITH, HIGH PEAK, SK23 0PH. U.K . T : +44 (0)1298 812456 F : +44 (0)1298 814945

ALL DIMENSIONS IN MILLIMETRES



LX032 CHAIN HOIST
ELECTRIC TRAVEL (TYPE 'CE') - Range 1

Steet Crane Model ref	Capacity kg	Speed m/min.	Power kW	Falls of Chain	Ø Chain mm	C1 mm	C2 mm	C3 mm	D mm	D1 mm	D2 mm	F1 min mm	F1 max mm	G1 mm	H mm	I1 mm	I2 mm	I3 mm	I4 mm	L mm	L1 mm	M mm	M1 mm	M2 mm	M4 mm	O mm	P mm	S mm	S1 mm	S2 mm	Ø T mm	V mm	V1 mm	Ø Wheel mm	Z mm	Max HOL m	Weight kg
LX032B-M53000-004-1	3000	4	3.0	2	10	260	323	304	236	218	70	82	200	34	15	164	186	236	190	176	77	715	95	104	20	312	162	352	281	164	24	163	223	80	35	16	140
LX032B-M53000-014-2	3000	4/1	3.0/0.7	2	10	260	353	304	236	218	70	82	200	34	15	149	171	236	190	176	77	715	95	104	20	312	162	352	280	165	24	163	223	80	35	16	140
LX032B-M53200-004-1	3200	4	3.0	2	11	260	323	304	236	218	70	82	200	34	15	164	186	236	190	176	77	715	95	104	20	312	162	352	281	164	24	163	223	80	35	16	140
LX032B-M53200-014-2	3200	4/1	3.0/0.7	2	11	260	353	304	236	218	70	82	200	34	15	149	171	236	190	176	77	715	95	104	20	312	162	352	280	165	24	163	223	80	35	16	140
LX032B-M54000-004-1	4000	4	3.0	2	11	260	322	334	236	218	70	82	200	34	20	173	177	245	181	176	86	735	95	104	20	318	167	352	280	165	24	163	223	80	40	16	150
LX032B-M54000-014-2	4000	4/1	3.0/0.7	2	11	260	352	334	236	218	70	82	200	34	20	173	177	245	181	176	86	735	95	104	20	318	167	352	280	165	24	163	223	80	40	16	150
LX032B-M55000-004-1	5000	4	3.0	2	11	260	322	334	236	218	70	82	200	34	20	173	177	245	181	176	86	735	95	104	20	318	167	352	281	164	24	163	223	80	40	16	158
LX032B-M55000-014-2	5000	4/1	3.5/0.8	2	11	260	352	334	236	218	70	82	200	34	20	173	177	245	181	176	86	735	95	104	20	318	167	352	280	165	224	163	223	80	40	16	158

FURTHER INFORMATION:

- SUPPLY 400V 3PH 50 Hz
- HOIST IP RATING IP55
- CONTROL PANEL IP RATING IP65 CEI-EN
- CONTROL VOLTAGE 48V
- OPERATING TEMPERATURE: -20°C TO +50°C
- MOTORS CLASS F INSULATION
- OVERLOAD CLUTCH SET AT 120% OF SWL.
- DUTY:

SPEED	%CDF	'M' RATING	FEM CLASS
SINGLE	55	M5	2m
DUAL	40/15	M5	2m

- HEIGHT OF LIFT (HOL) - 3m (STD) TO MAX VALUE AS SPECIFIED IN THE TABLE. CAN BE ORDERED WITH 1m INCREMENT.
- ADDITIONAL HOL MAY REQUIRE LARGER CHAIN BUCKET. DIMENSIONS 'C1', 'I3', 'S' AND WEIGHT MAY VARY THAN STANDARD SIZE.
- TROLLEY MOTOR SPEED - SINGLE SPEED AT EITHER 7m/min OR 14m/min OR DUAL SPEED AT 7/14m/min
TROLLEY MOTOR POWER - SINGLE SPEED AT 0.5kW OR DUAL SPEED AT 0.2/0.5kW

LX MODEL CODE BREAKDOWN

	LX03	2	B	M5	****	-***	-*	-1	-400	50	*	4	5	-0CE	-***	-*	-**
HOIST TYPE																	
NUMBER OF FALLS OF CHAIN																	
HOIST VERSION																	
HOIST DUTY																	
SAFE WORKING LOAD																	
HOIST SPEED																	
HOIST SPEED CODE																	
RANGE																	
SUPPLY POTENTIAL																	
SUPPLY FREQUENCY																	
COMPLIANCE																	
CONTROL POTENTIAL																	
MAX AMBIENT TEMPERATURE																	
HOIST CONSTRUCTION																	
TRAVERSE SPEED*																	
TRAVERSE SPEED CODE*																	
HEIGHT OF LIFT																	

F	DIM M4, MAX HOL COLUMN ADDED. TROLLEY MOTOR POWER AMENDED. REF ECO-00562 WHEREVER DIM H = 20 WAS 15. AMENDED AS PER MODEL.	PAK	26/02/2014
E	MODEL CODE UPDATED TO MATCH NEW PRICE LIST. REF ECO-00552	MAP	10/12/2013
D	SHT 1 REMOVED. 2000Kg MODEL MOVED TO DLX 1015. REF ECO-00515	GDM	16/07/2013
C	VERSION 'A' & 'B' SWAPPED. REF ECO-00445	SW	16/05/2011
B	DIMENSION LAYOUT CHANGED. REF ECO-00429	ANIL	07/02/2011
REV	DESCRIPTION	BY	DATE

Street Crane Co. Ltd


TITLE

LX032 CHAIN HOIST CE DATA SHEET
ELECTRIC TRAVEL (TYPE 'CE')

CONTRACT No.	
PART No.	DLX-1016
DRAWING No.	3 DLX-1016
	F SHT 2 OF 3

INFRINGEMENT OF COPYRIGHT. THIS DRAWING IS THE PROPERTY OF STREET CRANE COMPANY LTD AND MUST NOT BE COPIED OR SHOWN TO THIRD PARTIES WITHOUT THE WRITTEN PERMISSION OF STREET CRANE CO LTD, CHAPEL-EN-LE-FRITH, HIGH PEAK, SK23 0PH. U.K. T : +44 (0)1298 812456 F : +44 (0)1298 814945

ALL DIMENSIONS IN MILLIMETRES



LX032 CHAIN HOIST
ELECTRIC TRAVEL (TYPE 'CE') - Range 2

Steet Crane Model ref	Capacity kg	Speed m/min.	Power kW	Falls of Chain	Ø Chain mm	C1 mm	C2 mm	C3 mm	D mm	D1 mm	D2 mm	F1 min mm	F1 max mm	G1 mm	H mm	I1 mm	I2 mm	I3 mm	I4 mm	L mm	L1 mm	M mm	M1 mm	M2 mm	M4 mm	O mm	P mm	S mm	S1 mm	S2 mm	Ø T mm	V mm	V1 mm	Ø Wheel mm	Z mm	Max HOL m	Weight kg
LX032B-M53000-004-1	3000	4	3.0	2	10	260	323	304	236	218	70	201	300	34	15	164	186	236	190	176	77	715	95	104	20	312	162	352	281	164	24	163	223	80	35	16	140
LX032B-M53000-014-2	3000	4/1	3.0/0.7	2	10	260	353	304	236	218	70	201	300	34	15	149	171	236	190	176	77	715	95	104	20	312	162	352	280	165	24	163	223	80	35	16	140
LX032B-M53200-004-1	3200	4	3.0	2	11	260	323	304	236	218	70	201	300	34	15	164	186	236	190	176	77	715	95	104	20	312	162	352	281	164	24	163	223	80	35	16	140
LX032B-M53200-014-2	3200	4/1	3.0/0.7	2	11	260	353	304	236	218	70	201	300	34	15	149	171	236	190	176	77	715	95	104	20	312	162	352	280	165	24	163	223	80	35	16	140
LX032B-M54000-004-1	4000	4	3.0	2	11	260	322	334	236	218	70	201	300	34	20	173	177	245	181	176	86	735	95	104	20	318	167	352	280	165	24	163	223	80	40	16	150
LX032B-M54000-014-2	4000	4/1	3.0/0.7	2	11	260	352	334	236	218	70	201	300	34	20	173	177	245	181	176	86	735	95	104	20	318	167	352	280	165	24	163	223	80	40	16	150
LX032B-M55000-004-1	5000	4	3.0	2	11	260	322	334	236	218	70	201	300	34	20	173	177	245	181	176	86	735	95	104	20	318	167	352	281	164	24	163	223	80	40	16	158
LX032B-M55000-014-2	5000	4/1	3.5/0.8	2	11	260	352	334	236	218	70	201	300	34	20	173	177	245	181	176	86	735	95	104	20	318	167	352	280	165	224	163	223	80	40	16	158

FURTHER INFORMATION:

- SUPPLY 400V 3PH 50 Hz
- HOIST IP RATING IP55
- CONTROL PANEL IP RATING IP65 CEI-EN
- CONTROL VOLTAGE 48V
- OPERATING TEMPERATURE: -20°C TO +50°C
- MOTORS CLASS F INSULATION
- OVERLOAD CLUTCH SET AT 120% OF SWL.
- DUTY:

SPEED	%CDF	'M' RATING	FEM CLASS
SINGLE	55	M5	2m
DUAL	40/15	M5	2m

- HEIGHT OF LIFT (HOL) - 3m (STD) TO MAX VALUE AS SPECIFIED IN THE TABLE. CAN BE ORDERED WITH 1m INCREMENT.
- ADDITIONAL HOL MAY REQUIRE LARGER CHAIN BUCKET. DIMENSIONS 'C1', 'I3', 'S' AND WEIGHT MAY VARY THAN STANDARD SIZE.
- TROLLEY MOTOR SPEED - SINGLE SPEED AT EITHER 7m/min OR 14m/min OR DUAL SPEED AT 7/14m/min
TROLLEY MOTOR POWER - SINGLE SPEED AT 0.5kW OR DUAL SPEED AT 0.2/0.5kW

LX MODEL CODE BREAKDOWN

	LX03	2	B	M5	****	-***	-*	-2	-400	50	*	4	5	-0CE	-***	-*	-**
HOIST TYPE																	
NUMBER OF FALLS OF CHAIN																	
HOIST VERSION																	
HOIST DUTY																	
SAFE WORKING LOAD																	
HOIST SPEED																	
HOIST SPEED CODE																	
RANGE																	
SUPPLY POTENTIAL																	
SUPPLY FREQUENCY																	
COMPLIANCE																	
CONTROL POTENTIAL																	
MAX AMBIENT TEMPERATURE																	
HOIST CONSTRUCTION																	
TRAVERSE SPEED*																	
TRAVERSE SPEED CODE*																	
HEIGHT OF LIFT																	

F	DIM M4, MAX HOL COLUMN ADDED. TROLLEY MOTOR POWER AMENDED. REF ECO-00562 WHEREVER DIM H = 20 WAS 15. AMENDED AS PER MODEL.	PAK	26/02/2014
E	MODEL CODE UPDATED TO MATCH NEW PRICE LIST. REF ECO-00552	MAP	10/12/2013
D	SHT 1 REMOVED. 2000Kg MODEL MOVED TO DLX 1015. REF ECO-00515	GDM	16/07/2013
C	VERSION 'A' & 'B' SWAPPED. REF ECO-00445	SW	16/05/2011
B	DIMENSION LAYOUT CHANGED. REF ECO-00429	ANIL	07/02/2011
REV	DESCRIPTION	BY	DATE

Street Crane Co. Ltd

DATE	DRAWN	CHECKED	SCALE
23/09/2010	SW	CR	

TITLE
LX032 CHAIN HOIST CE DATA SHEET
ELECTRIC TRAVEL (TYPE 'CE')

CONTRACT No.	
PART No.	DLX-1016
DRAWING No.	3 DLX-1016 F SHT 3 OF 3