



Traglast kg	max. Hebezeug- gewicht kg	Portal- breite Außen A mm	Unterkante Last- träger UK mm	Portal- breite Lichte a mm	Bau- höhe B mm	Flansch- breite F mm	Spur S mm	Traversen- länge 1/2UK +150 mm TL mm	Anfahr- maß Ai mm	Rad- Ø mm	Gewicht ca.	
											Basis- kran kg	je 100 mm Bauhöhe kg
500	120	2500	2500	2090	2680	73	2180	1400	370	200	188	3,5
500	120	3000	2500	2590	2680	73	2680	1400	370	200	195	3,5
500	120	3500	2500	3090	2680	73	3180	1400	370	200	201	3,5
500	120	4000	2500	3590	2680	73	3680	1400	370	200	208	3,5
500	120	4500	2500	4090	2700	82	4180	1400	370	200	228	3,5
500	120	5000	2500	4590	2720	91	4680	1400	370	200	251	3,5
500	120	5500	2500	5090	2740	100	5180	1400	370	200	281	3,5
500	120	6000	2500	5590	2740	100	5680	1400	370	200	293	3,5
1000	160	2500	2500	2060	2720	91	2180	1400	370	200	245	4,5
1000	160	3000	2500	2560	2720	91	2680	1400	370	200	255	4,5
1000	160	3500	2500	3060	2720	91	3180	1400	370	200	264	4,5
1000	160	4000	2500	3560	2740	100	3680	1400	370	200	289	4,5
1000	160	4500	2500	4060	2740	100	4180	1400	370	200	300	4,5
1000	160	5000	2500	4560	2740	100	4680	1400	370	200	312	4,5
1000	160	5500	2500	5060	2760	110	5180	1400	370	200	345	4,5
1000	160	6000	2500	5560	2780	120	5680	1400	370	200	358	4,5
2000	180	2500	2500	2020	2780	120	2140	1400	420	250	327	4,5
2000	180	3000	2500	2520	2780	120	2640	1400	420	250	343	4,5
2000	180	3500	2500	3020	2780	120	3140	1400	420	250	358	4,5
2000	180	4000	2500	3520	2810	135	3640	1400	420	250	396	4,5
2000	180	4500	2500	4020	2810	135	4140	1400	420	250	415	4,5
2000	180	5000	2500	4520	2810	135	4640	1400	420	250	433	4,5
2000	180	5500	2500	5020	2840	150	5140	1400	420	250	486	4,5
2000	180	6000	2500	5520	2840	150	5640	1400	420	250	508	4,5
3200	250	2500	2500	2000	2870	160	2140	1400	420	150	456	6,0
3200	250	3000	2500	2500	2870	160	2640	1400	420	150	481	6,0
3200	250	3500	2500	3000	2870	160	3140	1400	420	150	506	6,0
3200	250	4000	2500	3500	2870	160	3640	1400	420	150	532	6,0
3200	250	4500	2500	4000	2900	170	4140	1400	420	150	594	6,0
3200	250	5000	2500	4500	2900	170	4640	1400	420	150	623	6,0
3200	250	5500	2500	5000	2900	170	5140	1400	420	150	652	6,0
3200	250	6000	2500	5500	2900	170	5640	1400	420	150	682	6,0
4000	300	2500	2500	1990	2900	170	2140	1400	420	200	456	7,0
4000	300	3000	2500	2490	2900	170	2640	1400	420	200	506	7,0
4000	300	3500	2500	2990	2900	170	3140	1400	420	200	563	7,0
4000	300	4000	2500	3490	2900	170	3640	1400	420	200	592	7,0
4000	300	4500	2500	3990	2940	180	4140	1400	420	200	664	7,0
4000	300	5000	2500	4490	2940	180	4640	1400	420	200	698	7,0
4000	300	5500	2500	4990	2940	180	5140	1400	420	200	732	7,0
4000	300	6000	2500	5490	2940	180	5640	1400	420	200	766	7,0
5000	350	2500	2500	1990	2940	180	2140	1400	420	200	542	9,0
5000	350	3000	2500	2490	2940	180	2640	1400	420	200	612	9,0
5000	350	3500	2500	2990	2990	190	3140	1400	420	200	688	9,0
5000	350	4000	2500	3490	2990	190	3640	1400	420	200	728	9,0
5000	350	4500	2500	3990	2990	190	4140	1400	420	200	768	9,0
5000	350	5000	2500	4490	2990	190	4640	1400	420	200	808	9,0
5000	350	5500	2500	4990	2990	190	5140	1400	420	200	848	9,0
5000	350	6000	2500	5490	2990	190	5640	1400	420	200	888	9,0

Konstruktions- und Maßänderungen vorbehalten

Änderungsindex "A"